

APLITAPE LOW TACK

HEAVYWEIGHT PAPER APPLICATION TAPE

It is standard weight saturated paper coated with a very low tack rubber adhesive designed specifically as a protective masking of wide format digital graphics and large vinyl graphics.

TECH DATA SHEET

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper <i>facestock</i>	100-113 microns (4.0 -4.5 mils)
Caliper <i>facestock + adhesive</i>	125-138 microns (5.0 - 5.5 mils)
Adhesion to Steel*	7 - 9 N/100mm (6 - 8oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance	50
Shelf Life**	1 year

FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Perform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

APPLICATIONS

- Premask for large vinyl graphics and digital prints.
- Protective masking for acrylic, high pressure laminates, PETG, polycarbonates and other plastics.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.