

Technical Data Sheet

Issue date: 05/01/2005 Date last modification: 17/12/2014

03529 ETCH GLASS PTA/PTAS/PTF SERIES ASP26 PERMANENT WK120

Face Material

VISCOM - RI-MARK

Self-adhesive material for plotter. Polymeric translucent vinyl with metallic flakes.

Translucent polymeric vinyl Type

Colour and Finish 3 colours available ISO-536 Weight 100 g/m² ±10% ISO 534-80 **Thickness** 80 µ ±10%

Adhesive

Permanent solvent acrylic featuring high cohesion and good water resistance.

Reference ASP26 permanent Acrylic permanent Type

Min. Appl. Temp. +10°C

-20°C/+130°C Service Temp. Shear High

Tack Medium N/inch² Final Adhesion High N/inch

Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

PP-032 - ISO Weight 120 g/m²

536 ±10%

Thickness 108 μ ±10% ISO 534 DIN 53 147-64 Transparency n.a. %

Applications

Translucent Etch simulation effect for glass decoration. 5 years outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.

Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of $22^{\circ}C \pm 2^{\circ}C$ and $50 \pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



