

Laminated Frontlit 510gr

PRODUCT: YFL4470

FEATURES / APPLICATIONS:

- Cost effective Banner
- For short-term use - outdoor banners, signs & indoor displays
- Matte & gloss surface available

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	510g/m ²	15oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	330 x 550 dtex	300 x 500 denier
Tensile Strength	DIN EN ISO 1421	729x595 N/5cm	82x67 lbs/inch
Tear Strength	DIN 53363	120x115 N	27x 26lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 320cm	126 Inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty