

## Premium Mesh With Liner

PRODUCT: TRL6330

### FEATURES / APPLICATIONS:

- 37% air-flow through
- Coming with a PVC backing which makes the feeding and printing much easier
- Widely used for scaffolding, theatrical, wall wrapping ,TV backdrops, hanging display& large format advertisement

### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	430g/m <sup>2</sup>	12.6oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1520x1250 N/5cm	170x140 lbs/inch
Tear Strength	DIN 53363	280x223N	63x50lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 500cm	197 inch

### INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
□	□	□	□
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty